

MIXTURES OF VEGETABLE OIL AND USED FRYING OIL AS FEEDSTOCK FOR BIODIESEL PRODUCTION IN THAILAND

Piyanuch Nakpong* and Sasiwimol Wootthikanokkhan

Received: Jan 12, 2010; Revised: Apr 24, 2010; Accepted: Apr 27, 2010

Abstract

In this study, used frying oil was mixed with 3 fresh vegetable oils at various blending ratios (0.03-0.20 v/v) in order to study the feasibility of the biodiesel production from the mixed oil feedstocks by KOH-catalyzed methanolysis and also examine the effect of used frying oil content in oil feedstock on the reaction. The methanolysis was carried out with fresh vegetable oils (coconut, sunflower, and roselle oils), used frying oil (palm oil) and the mixtures of fresh vegetable oils and used frying oil in order to compare the methyl ester content in biodiesel products. The results revealed that biodiesels could be successfully produced from mixed oil feedstocks and the used frying oil- to-fresh vegetable oil ratio of 0.03 v/v was required in order to produced coconut-used frying oil and roselle-used frying oil biodiesels having methyl ester content higher than the minimum (96.5% w/w) prescribed by European Standard EN 14214 (2008) and Thai biodiesel (B100) specifications. The used frying oil content in oil feedstock had the negative effect on the reaction which resulted in the reduction of methyl ester content in biodiesel products. This was due to the free fatty acid and water in used frying oil caused soap formation which interfered with the reaction. The measured properties of biodiesels produced from mixed oil feedstocks at blending ratio of 0.03 v/v met with Thai biodiesel (B100) specifications, with the exception of the slight lower methyl ester content and lower viscosity of the sunflower-used frying oil biodiesel and the coconut-used frying oil biodiesel, respectively.

Keywords: Biodiesel, methanolysis, used frying oil, methyl ester content, used frying oil-to-fresh vegetable oil ratio

Introduction

Due to the depletion of world petroleum reserves, the rapidly increasing prices of petroleum, and the growing concern for the environment, the search for alternative fuels has currently attracted much attention (Meher *et al.*, 2006a; Balat and Balat, 2008). Among


the alternative possible sources, biodiesel is becoming increasingly important as an alternative fuel in diesel substitution. It can be used in public transportation and performing farm engines (Tomasevic and Siler-Marinkovic, 2003). Biodiesel is monoalkyl esters of long

Department of Chemistry, Faculty of Science and Technology, Rajamangala University of Technology Krungthep, Bangkok 10120, Thailand. Tel.: 0-2287-9600 ext. 1202, 1204; Fax: 0-2287-9600 ext. 1202, 1205; E-mail: piyanuch.n@rmutk.ac.th

* Corresponding author

chain fatty acids. It can be produced from vegetable oils and animal fats. These oils and fats have high viscosity (approximately 11-17 times higher than petroleum diesel) (Meher *et al.*, 2006a). Their high viscosity causes many problems in diesel engines when they are directly used as fuel. The conversion of these oils and fats to biodiesels leads to the reduction in viscosity to the acceptable level which results in the improvement of atomization, fuel vaporization, and combustion (Ramadhas *et al.*, 2005a). The characteristics of resulting biodiesel are close to those of petroleum diesel. Some important properties of biodiesel depend on the fatty acid composition of oil feedstock. Different types of oils have different types of fatty acids (Balat and Balat, 2008). The fatty acid composition of oil plays a significant role in the performance of biodiesel in diesel engines. Saturation fatty acid methyl esters improve stability and increase the cetane number and cloud point. On the other hand, more polyunsaturation reduces the stability, cetane number, and cloud point (Ramadhas *et al.*, 2005b).

The most common way of producing biodiesel is the alkali-catalyzed transesterification of vegetable oils and animal fats (Gerpen, 2005; Balat and Balat, 2008). The general equation for this reaction can be represented as follows:



The transesterification is also called alcoholysis. If methanol or ethanol is used as the reactant, it is called methanolysis or ethanolysis, respectively. Vegetable oils and animal fats are composed primarily of the triglycerides (Dorado *et al.*, 2004). In this reaction, triglycerides react with alcohol to produce alkyl esters and glycerol, the valuable by-product used in the soap, pharmaceutical, and cosmetic industries (Lewis, 1993). The most often used alcohol is methanol due to its low price and its physical and chemical advantages (Ma and Hanna, 1999). Sodium and potassium hydroxides are the commonly

used alkaline catalysts for this process (Gerpen, 2005; Ramadhas *et al.*, 2005a). It is known that the important factors that affect the alkali-catalyzed transesterification are the free fatty acid (FFA) and water contents (Freedman *et al.*, 1984; Ma and Hanna, 1999; Meher *et al.*, 2006a). To carry this reaction to completion, the oils having a FFA content less than 1% is required (Ghadge and Raheman, 2005; Tiwari *et al.*, 2007) and all materials should be substantially anhydrous (Meher *et al.*, 2006a).

Nowadays, various kinds of oils are used to produce biodiesel commercially such as palm, rapeseed, soybean, and sunflower oils. However, many published papers have reported that there are other oils which can be used for this purpose including jatropha, rice barn, karanja, cardoon, pumpkin seed, rubber seed, and used frying oils (Encinar *et al.*, 1999; Ramadhas *et al.*, 2005b; Leung and Guo, 2006; Meher *et al.*, 2006b; Krishnakumar *et al.*, 2008; Oliveira *et al.*, 2008; Schinas *et al.*, 2009). At present large quantities of used frying oils are produced from many places such as restaurants and households. These oils are reused several times and disposed of in inappropriate ways which cause health and environmental problems. One of several possibilities for utilization of these waste oils is to use them as feedstock for biodiesel production. This results in the alleviation of those problems. Actually, the waste used frying oil is one of the economical feedstocks for biodiesel production. However, it has different properties from the fresh refined or non-refined vegetable oils due to its higher impurities, FFA and water contents (Leung and Guo, 2006; Issariyakul *et al.*, 2008). Hence, it is not suitable for use as feedstock in the alkali-catalyzed transesterification due to the FFA and water causing the formation of soap which consumes the catalyst and reduces catalyst efficiency. The soap increases the viscosity of the reactant and the formation of gels, and interferes in the separation of glycerol from the methyl ester layer. These result in a low yield and low quality of biodiesel (Ma and Hanna, 1999; Meher *et al.*, 2006a; Issariyakul *et al.*, 2008). Although,

biodiesel can be produced from the oils having a high FFA content via acid-catalyzed transesterification, a longer time and acid-resistible reactor are required (Issariyakul *et al.*, 2008). To overcome this obstacle, the reduction of the FFA and water contents in used frying oil is necessary. One of the alternative ways to achieve this purpose is to blend it with the fresh vegetable oil having lower FFA and water contents. This is the way to make use of the used frying oil for the biodiesel production via a simple one-step alkali-catalyzed process. Recently, reports in the literature have shown that a satisfactory result was obtained when the biodiesel was produced from the mixture of canola oil and used cooking oil (Issariyakul *et al.*, 2008).

As a result, our research team was interested in the utilization of the mixture of fresh vegetable oil and used frying oil as feedstock for biodiesel production via alkali-catalyzed methanolysis. The fresh non-refined vegetable oils such as coconut, sunflower, and roselle oils were used. The objectives of this study are: (a) to study the feasibility of the mixtures of fresh vegetable oil and used frying oil as the feedstock for biodiesel production; (b) to investigate the effect of the used frying oil content in oil feedstock on the reaction.

Materials and Methods

Materials

The coconut, sunflower, and roselle oils were obtained from Sangsook Industry Company Limited (Bangkok, Thailand), the supermarket (Bangkok, Thailand), and Payakkaram Temple (Suphanburi Province, Thailand), respectively. The used frying oil (palm oil) was purchased from a local restaurant in Bangkok. The analytical reagent (AR) grade methanol, potassium hydroxide, and n-heptane were purchased from Ajax Finechem (New South Wales, Australia). The methyl esters such as methyl heptadecanoate, methyl esters of lauric, myristic, palmitic, stearic, oleic, linoleic, and linolenic acids were gas chromatography reference standard and

they were purchased from Fluka (Buchs, Switzerland).

Equipment

The reactions were carried out in a laboratory-scale setup. A 250 mL 3-necked flat-bottom flask was used as a reactor. Two of the 3 necks were equipped with a condenser and thermometer whereas the other was used as an inlet for the reactants. The reaction mixture was heated and well-stirred at 600 rpm (Vicente *et al.*, 2005) by a hot plate with a magnetic stirrer (Fisher scientific Model 11-302-50 SHP).

Experimental Conditions

The experiments were designed to study the feasibility of 3 mixtures of fresh non-refined vegetable oil and used frying oil as feedstock in the alkali-catalyzed methanolysis and the effect of the used frying oil content in oil feedstock on the reaction. For the latter purpose, the methanolysis of each fresh vegetable oil and used frying oil was also conducted to compare with the mixed oil feedstocks. In this study, potassium hydroxide (KOH) was used as a catalyst for all experiments and the other reaction conditions are shown in Table 2.

Alkali-catalyzed Methanolysis

The oil feedstocks, methanol, and potassium hydroxide were used in amounts established for each experiment. The oil was charged into the reactor and heated to the desired temperature. The solution of potassium hydroxide in methanol was prepared freshly in order to avoid the moisture absorbance and to maintain the catalytic activity (Meher *et al.*, 2006a, 2006b). The methanolic solution was then gradually added to the preheated oil. After the completion of the addition, the measurement of time was started. Heating and stirring were continued at atmospheric pressure. After the reaction, the product mixture was allowed to settle overnight under gravity in the separatory funnel. It was separated into 2 layers. The top layer consisted of methyl esters, residual unreacted methanol, catalyst, and impurities, whereas the bottom layer contained a mixture of glycerol, an excess of unreacted

methanol, catalyst, and impurities. The glycerol layer was drawn off and the methyl ester layer was then washed gently with hot distilled water at 60°C until the washing water had a pH value that was similar to that of distilled water. The pH of the washing water was measured by pH-indicator strips. This confirmed that the alkaline catalyst was completely removed. The wet methyl ester layer was then dried at 70°C by vacuum rotary evaporator (BUCHI Rotavapor Model R110, Flawil, Switzerland). Finally, the methyl ester content of each biodiesel product was determined by gas chromatography (GC).

Analytical Methods of Methyl Ester Content

Sunflower, Roselle, and used Frying Oils, the Mixture of Sunflower Oil and used Frying Oil, and the Mixture of Roselle Oil and used Frying Oil as Feedstocks

The methyl ester contents of biodiesels produced from these oils were determined by European Standard method EN 14103 (2003).

The Coconut Oil and the Mixture of Coconut Oil and used Frying Oil as Feedstocks

The methyl ester contents of biodiesels produced from these oil feedstocks were determined by GC technique. The gas chromatograph of Agilent 6890N that equipped with a flame ionization detector and a capillary column of crosslinked polyethylene glycol (HP-INNOWax, 25 m x 0.20 mm x 0.2 µm). The gas chromatograph oven was kept at 200°C for 5 min. The carrier gas was helium at a flow rate of 0.5 ml/min. The analysis was carried out by injecting 1 µL of sample solution into the gas chromatograph. The n-heptane was used as the solvent for preparing the sample solution. Each methyl ester in the sample was identified by comparing its retention time with the retention time of the standard of the methyl ester of FFAs. Methyl heptadecanoate was used as the internal standard for the methyl ester content determination.

Properties of Biodiesels

The biodiesels produced from the mixtures of fresh vegetable oil and used frying oil at the blending ratio of 0.03 v/v were sent to the Quality Control Division of PTT Public Company Limited to determine their properties by using standard methods. The results in comparison with those of Thai biodiesel (B100) specifications are shown in Table 3.

Results and Discussion

Characterization of Oil Feedstocks

In this study, the used frying oil was settled until the solid impurities were completely precipitated and the oil layer was then separated. All fresh vegetable oils and used frying oil were viscous and different in color. The sunflower and roselle oils were yellow whereas the coconut and used frying oils were brown and black in color, respectively. These oils were characterized by fatty acid composition, density, viscosity, FFA, and water contents. The results are presented in Table 1.

The results showed that the fresh vegetable oils and used frying oil had a higher viscosity than the average value of Thai petroleum diesel (3.068 mm²/s) by approximately 9-12 times. The used frying oil had higher FFA and water contents compared with those of fresh vegetable oils and the limit required for alkali-catalyzed transesterification. Hence, this used frying oil was not suitable to be the feedstock in the reaction.

Alkali-catalyzed Methanolysis

Effect of used frying oil content in oil feedstock

In this study, fresh vegetable oils, used frying oil and the mixtures of fresh vegetable oil and used frying oil were used as feedstocks for alkali-catalyzed methanolysis. The used frying oil-to-fresh vegetable oil ratios were 0.03, 0.05, 0.10, 0.15, and 0.20 v/v. The averages of the methyl ester contents in the biodiesel products are shown in Table 2.

It was found that the methyl ester contents reached the maximum values when the fresh vegetable oils were used as feedstocks. These results were in accordance with the results found by other researchers (Issariyakul *et al.*, 2008). On the other hand, used frying oil provided the lowest methyl ester content for all reaction conditions. The methyl ester content decreased with the increase in the used frying oil content in the oil feedstock. This similar trend was also obtained for all mixed oil feedstocks. In addition, it was observed that the light gelatinous precipitate (soap) and the emulsion between the biodiesel and washing water layers were occurred during the reaction and washing step, respectively, when the used frying oil and mixed oils were used as feedstocks. The

amount of the gelatinous precipitate increased with further increased in the used frying oil content in oil feedstock. On the other hand, in the case of fresh vegetable oils, the light gelatinous precipitate and the emulsion formation were not observed during the reaction and washing step, respectively. These were due to the further increase of the used frying oil content which resulted in the increase of FFA and water contents in the oil feedstocks. The FFA and water caused the soap formation which interfered with the reaction as well as the separation of glycerol from the biodiesel product. It resulted in the low methyl ester content. Therefore, all these results indicated that the used frying oil content had a negative effect on the reaction and the FFA and water contents played a

Table 1. Properties of oil feedstocks

Property	Method	Coconut oil	Sunflower oil	Roselle oil	Used frying oil
Fatty acid composition (%) ^a	AOAC (2005), 963.22, 969.33				
(i) Caprylic acid (C8:0)		3.4			
(ii) Capric acid (C10:0)		3.2			
(iii) Lauric acid (C12:0)		32.7			
(iv) Myristic acid (C14:0)		18.4			1.0 ^b
(v) Palmitic acid (C16:0)		13.1	6.2	18.2	42.8 ^b
(vi) Stearic acid (C18:0)		3.6	3.8	4.1	4.5 ^b
(vii) Oleic acid (C18:1)		12.9	38.6	33.3	40.5 ^b
(viii) Linoleic acid (C18:2)		4.4	50.1	38.2	10.1 ^b
(ix) Linolenic acid (C18:3)				2.1	0.2 ^b
Density at 15°C, kg/m ³	ASTM D 4052-96 (1996)	914.4	921.8	919.9	914.8
Kinematic viscosity at 40°C, mm ² /s	ASTM D 445-06 (2006)	27.52	32.68	36.35	38.40
Free fatty acid content, % w/w	AOAC (2000), 940.28	0.60	04.5	0.67	1.90
		(as lauric acid)	(as lauric acid)	(as lauric acid)	(as lauric acid)
Water content, % w/w	AOAC (1990), 984.20	0.0146	0.0840	0.0870	0.1077

^a Other fatty acids were present in amounts of < 1%.

^b Ma and Hanna, 1999

^c Reaction condition: Methanol:oil of 8:1, catalyst concentration of 1.5% w/w of oil, 60°C, and 60 minutes

catalyzed transesterification which can be used to prevent the soap formation (Canakci and Genpen, 1999; Zheng *et al.*, 2006). However, this process required the longer reaction time and the acid-resistible reactor (Issariyakul *et al.*, 2008). Therefore, in this study, the utilization of the mixture of fresh vegetable oil and used frying oil as feedstock is an alternative way to make use of the used frying oil for the biodiesel production through a simple one-step and low-cost alkali-catalyzed process. Although, in this study, the ratio of 0.03 v/v seems to consume only a little amount of used frying oil, in the industrial biodiesel production, this ratio leads to a large scale consumption of used frying oil.

Properties of Biodiesels Produced from the Mixtures of Fresh Vegetable Oil and Used Frying Oil

Table 3 shows that the measured properties of the 3 biodiesels were within the

limits prescribed by Thai specifications, with the exception of the slight lower methyl ester content and lower viscosity of the sunflower-used frying oil biodiesel and the coconut-used frying oil biodiesel, respectively. However, the viscosity of coconut-used frying oil biodiesel was very close to that of Thai petroleum diesel and it was within the limits of ASTM D 6751-07b (2007) (1.9-6.0 mm²/s). This was because the coconut triglyceride consisted of 57.5% short chain fatty acids comprised primarily of lauric acid whereas the sunflower and roselle triglycerides consisted chiefly of long chain fatty acids such as oleic and linoleic acids. Thus, biodiesel obtained from the mixture of coconut oil and used frying oil contained a high proportion of low molecular weight methyl esters, especially methyl laurate. On the other hand, the other 2 biodiesels contained mainly methyl oleate and methyl linoleate (high molecular weight methyl esters). This resulted in the lower viscosity of biodiesel produced from the mixture of

Table 3. Measured properties of biodiesel products in comparison with Thai biodiesel (B100) specifications

Property	Method	Limit	Biodiesel		
			Coconut-used frying oil	Sunflower-used frying oil	Roselle-used frying oil
Methyl ester content, % w/w	EN 14103 (2003)	96.5	97.5	95.4	97.2
Density at 15°C, kg/m ³	ASTM D 4052-96 (1996)	860-900	879.4	883.9	886.2
Kinematic viscosity at 40°C, mm ² /s	ASTM D 445-06 (2006)	3.5-5	3.057	4.286	4.549
Flash point, °C	ASTM D 93-02a (2002)	120 min	> 120	> 120	> 120
Copper strip corrosion (3 h at 50°C)	ASTM D 130-94 (1994)	No. 1 max	1a	1a	1a
Water content, mg/kg	ISO 12937 (2000)	500 max	420	440	390
Total acid number, mg KOH/g	ASTM D 664-01 (2001)	0.5 max	0.28	0.15	0.31
Linolenic methyl ester content, % w/w	EN 14103 (2003)	12.0 max	0	0	2.088

coconut oil and used frying oil as compared with the other 2 biodiesels.

Conclusions

This study demonstrated that the mixtures of fresh vegetable oil (coconut or sunflower or roselle oil) and used frying oil could be used as feedstock for biodiesel production via alkali-catalyzed methanolysis. The used frying oil content in oil feedstocks had a negative effect on the reaction which was due to its higher FFA and water contents. The blending ratio of 0.03 v/v provided the best results, especially for the biodiesels produced from the mixtures of coconut-used frying oil and roselle-used frying oil. The measured properties of biodiesels met with Thai biodiesel (B100) specifications, with the exception of the slight lower methyl ester content and lower viscosity of sunflower-used frying oil biodiesel and coconut-used frying oil biodiesel, respectively. Therefore, these mixtures of fresh vegetable oil and used frying oil can be recommended as a supplementary oil feedstock for biodiesel production in Thailand if engine performance tests provide satisfactory results.

Acknowledgements

The authors thank Sangsook Industry Company Limited and Payakkaram Temple, which provided coconut and roselle oils for biodiesel production, respectively, and the Quality Control Division of PTT Public Company Limited, which performed the standard test to determine the biodiesel properties. Finally, the authors wish to thank to Rajamangala University of Technology Krungthep for the financial support.

References

- AOAC 984.20. (1990). Official Methods of Analysis. AOAC International, Gaithersburg, MD, USA.
- AOAC 940.28. (2000). Official Methods of Analysis. AOAC International, Gaithersburg, MD, USA.
- AOAC 963.22, 969.33. (2005). Official Methods of Analysis. AOAC International, Gaithersburg, MD, USA.
- ASTM D 130-94. (1994). Standard Test Method for Detection of Copper Corrosion from Petroleum Products by the Copper Strip Tarnish Test. Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- ASTM D 4052-96. (1996). Standard Test Method for Density and Relative Density of Liquids by Digital Density Meter. Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- ASTM D 664-01. (2001). Standard Test Method for Acid Number of Petroleum Products by Potentiometric Titration. Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- ASTM D 93-02a. (2002). Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester. Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- ASTM D 445-06. (2006). Standard Test Method for Kinetic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity). Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- ASTM D 6751-07b. (2007). Standard Specification for Biodiesel Fuel Blend Stock (B100) for Middle Distillate Fuels. Annual Book of ASTM Standards. ASTM International, West Conshohocken, PA, USA.
- Balat, M. and Balat, H. (2008). A critical review of bio-diesel as a vehicular fuel. *Energy Convers. Manage.*, 49:2727-2741.
- Canakci, M. and Gerpen, J.V. (1999). Biodiesel production via acid catalyst. *Trans. Am. Soc. Agric. Eng.*, 42(5): 1203-1210.
- Canakci, M. and Gerpen, J.V. (2001). Biodiesel production from oils and fats with high free fatty acids. *Trans. Am. Soc. Agric. Eng.*

- Eng., 44(6): 1429-1436.
- Dorado, M.P., Ballesteros, E., López, F.J., and Mittelbach, M. (2004). Optimization of alkali-catalyzed transesterification of Brassica Carinata oil for biodiesel production. *Energy Fuels*, 18(1):77-83.
- Encinar, J.M., González, J.F., Sabio, E., and Ramiro, M.J. (1999). Preparation and properties of biodiesel from Cynara cardunculus L. oil. *Ind. Eng. Chem. Res.*, 38:2927-2931.
- European Standard EN 14103. (2003). Fat and oil derivatives. Fatty Acid Methyl Esters (FAME). Determination of ester and linolenic acid methyl ester contents. European Committee for Standardization, Brussels, Belgium.
- European Standard EN 14214. (2008). Automotive fuels. Fatty acid methyl esters (FAME) for diesel engines. Requirements and test methods. European Committee for Standardization, Brussels, Belgium.
- Freedman, B., Pryde E.H., and Mounts T.L. (1984). Variables affecting the yields of fatty esters from transesterified vegetable oils. *J. Am. Oil Chem. Soc.*, 61(10): 1638-1643.
- Gerpen, J.V. (2005). Biodiesel processing and production. *Fuel Process. Technol.*, 86:1097-1107.
- Ghadge, S.V. and Raheman, H. (2005). Biodiesel production from mahua (*Madhuca indica*) oil having high free fatty acid. *Biomass Bioenerg.*, 28:601-605.
- ISO 12937. (2000). Petroleum products – Determination of water – Coulometric Karl Fischer titration method. International Organization for Standardization, Geneva, Switzerland.
- Issariyakul, T., Kulkarni, M.G., Meher, L.C., Dalai, A.K., and Bakhshi, N.N. (2008). Biodiesel production from mixtures of canola oil and use cooking oil. *Chem. Eng. J.*, 140:77-85.
- Krishnakumar, J., Venkatachalapathy, V.S.K., and Elancheliyan, S. (2008). Technical aspects of biodiesel production from vegetable oils. *Therm. Sci.*, 12:159-169.
- Leung, D.Y.C. and Guo, Y. (2006). Transesterification of neat and used frying oil: Optimization for biodiesel production. *Fuel Process. Technol.*, 87:883-890.
- Lewis, R.J., Sr. (1993). *Hawley's Condensed Chemical Dictionary*. 12th ed. Van Nostrand Reinhold Company, NY, 1275p.
- Ma, F. and Hanna, M.A. (1999). Biodiesel production : a review. *Bioresource Technol.*, 70:1-15.
- Meher, L.C., Sagar, D.V., and Naik, S.N. (2006a). Technical aspects of biodiesel Production by Transesterification—a review. *Renew. Sust. Energ. Rev.*, 10(3): 248-268.
- Meher, L.C., Dharmagadda, V.S.S., and Naik, S.N. (2006b). Optimization of alkali-catalyzed transesterification of Pongamia pinnata oil for production of biodiesel. *Bioresource Technol.*, 97:1392-1397.
- Oliveira, L.S., Franca, A.S., Camargos, R.R.S., and Ferraz, V.P. (2008). Coffee oil as a potential feedstock for biodiesel production. *Bioresource Technol.*, 99: 3244-3250.
- Ramadhas, A.S., Muraleedhaean, C., and Jayaraj, S. (2005a). Performance and emission evaluation of a diesel engine fueled with methyl esters of rubber seed oil. *Renew. Energ.*, 30:1789-1800.
- Ramadhas, A.S., Jayaraj, S., and Muraleedharan, C. (2005b). Biodiesel production from high FFA rubber seed oil. *Fuel*, 84:335-340.
- Schinas, P., Karavalakis, G., Davaris, C., Anastopoulos, G., Karonis, D., Zannikos, F., Stournas, S., and Lois, E. (2009). Pumpkin (*Cucurbita pepo* L.) seed oil as an alternative feedstock for the production of biodiesel in Greece. *Biomass Bioenerg.*, 33(1):44-49.
- Tiwari, A.K., Kumar, A., and Raheman, H. (2007). Biodiesel production from jatropha oil (*Jatropha curcas*) with high free fatty acids: An optimized process. *Biomass Bioenerg.*, 31:569-575.

- Tomasevic, A.V. and Siler-Marinkovic, S.S. (2003). Methanolysis of used frying oil. *Fuel Process. Technol.*, 81:1-6.
- Vicente, G., Martinez, M., Aracil, J., and Esteban, A. (2005). Kinetics of sunflower oil methanolysis. *Ind. Eng. Chem. Res.*, 44:5447-5454.
- Wang, Y., Ou, S., Liu, P., and Zhang, Z. (2007). Preparation of biodiesel from waste cooking oil via two-step catalyzed process. *Energy Convers. Manage.*, 48:184-188.
- Zheng, S., Kates, M., Dube, M.A., and McLean, D.D. (2006). Acid-catalyzed production of biodiesel from waste frying oil. *Biomass Bioenerg.*, 30(3):267-272.